



<u> 70000</u>

Θ

 $\Theta \Theta \Theta \Theta$ 

 $\begin{array}{c} \Theta \Theta \Theta \Theta \\ \overline{\Theta} \Theta \Theta \Theta \end{array}$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta$ 

 $\begin{array}{c} \Theta \Theta \Theta \Theta \\ \Theta \Theta \Theta \Theta \\ \Theta \Theta \Theta \Theta \end{array}$ 

 $\begin{array}{c} \Theta \Theta \Theta \Theta \\ \Theta \Theta \Theta \Theta \end{array}$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta$ 

 $\begin{array}{c} \Theta \Theta \Theta \Theta \\ \Theta \Theta \Theta \Theta \\ \Theta \Theta \Theta \Theta \end{array}$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta$ 

 $\begin{array}{c} \Theta \Theta \Theta \Theta \\ \Theta \Theta \Theta \Theta \end{array}$ 

 $\Theta \Theta \Theta \Theta$ 

 $\begin{array}{c} \Theta \Theta \Theta \Theta \\ \Theta \Theta \Theta \Theta \end{array}$ 

 $\Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta \Theta \Theta \Theta \Theta \Theta$ 

 $\underline{\ominus \Theta \Theta \Theta \Theta \Theta \Theta}$ 

## LED RGB Controller EP-RGB/RGBY(W)-MS

CEOROHS

 $\Theta \Theta \Theta \Theta \Theta \Theta \Theta \Theta \Theta \Theta \Theta$ 

 $\begin{array}{c} \Theta \Theta \Theta \Theta \\ \Theta & \Theta \Theta \end{array}$ 

 $\Theta^{\Theta}\Theta$ 

Θ

 $\Theta \Theta \Theta \Theta \Theta \Theta \Theta$ 

 $\Theta \Theta \Theta$ 

 $\bigcirc$ 

ΘΘ

Θ

EP-RGB/RGBY(W)-MS Series full-color LED controllers feature high-reliability and cost-effective, mainly come in two types for constant voltage and constant current series. The controllers has maximium fourchannel output functioning as RGBY(W) controller and RGB controller if only three channels output are used.

## SPECIFICATIONS

- 1. 256 levels of grey scales for RGB/RGBY full-color changing gently, smooth, subtlely and softly without any flash.
- 2. 9 dynamic modes, gradient, skipping, etc., 4 static colors(R,G,B,Y)
- 3. To stop at a single static color(R,G,B,Y available), speed & brightness adjustable with the function Pause.
- 4. Can connect with other externer controllers, such as externer switches.
- 5. work with power repeater to expand output unlimitely.

## € EPIC™ GLOBAL SYSTEM

8

## **BEYOND THE LIMITS!**

2101 West Central Blvd. Orlando, Florida 32905 Tel: 1.800.507.5714 Fax: Wesite: www.yourdomain.com